

AVKOPACK® 1402



CHARACTERISTICS

Gland packing braided by cotton yarn, impregnated with mineral products. Cotton is well known, and is the most commonly applied vegetable fibre, which has high flexibility and ability for braiding. The mineral products used as impregnants have excellent lubricating properties.

Application

AVKOPACK 1402 may have round or square section. The braiding may be with a diagonal or multi-layer structure. The gland packing is soft and flexible, properties that make it universally applicable in any kind of equipment.

The packing is suitable to be used as a seal for industrial, potable, waste, or sea water, and for dry industrial or inert gasses.

Advantages

AVKOPACK 1402 is widely applied for the sealing of installations and equipment in the chemical, pharmaceutical, food processing, power, and other industries.

Technical parameters

Working temperature:	up to +120°C
Working pressure:	
- for rotary - pumps:	20 bar
- for piston - pumps:	8 bar
- for armature:	40 bar
pH:	5 – 9
V:	10 m/s
Standard dimensions:	from 4 x 4 mm to 50 x 50 mm

Quality Control

The whole production process is supervised in accordance with the Quality System ISO 9001, ISO 14001, OHSAS 18001.

Human hazardous

Not registered.

The information listed in this technical data sheet is based on our company's trials and experience. AVKO JSC is not to be held responsible for poor installation or application in media combining complexity of factors whose total exceeds the general qualities of the product. Our technical and sales representatives will assist any client in need of a product with a peculiar application.