

AVKOPACK[®] 1502



CHARACTERISTICS

Dry gland packing braided by textured glass yarn.

Application

AVKOPACK 1502 is used for static sealing and hermetisation of immovable joints of various machines and apparatus when a resistance to high temperature is required.

The packing is a substitute of the widely used dry asbestos packing in the temperature range up to 450°C.

It is used for sealing air, inert gases, neutral steam, water steam, organic solvents and etc.

Advantages

The packing is widely used in sealing immovable joints in all spheres of industries - the chemical, the pharmaceutical, the oil refining, food processing and power supplying industries, in the metallurgy, the cellulose industry and etc.

Technical parameters

<i>Working temperature:</i>	<i>up to +500°C</i>
<i>pH:</i>	<i>6 – 11</i>
<i>Standard dimensions:</i>	<i>from 4 x 4 mm to 50 x 50 mm</i>

Quality Control

The whole production process is supervised in accordance with the Quality System ISO 9001, ISO 14001, OHSAS 18001.

Human hazardous

Not registered.

The information listed in this technical data sheet is based on our company's trials and experience. AVKO JSC is not to be held responsible for poor installation or application in media combining complexity of factors whose total exceeds the general qualities of the product. Our technical and sales representatives will assist any client in need of a product with a peculiar application.