

## AVKOPACK® 1513



### CHARACTERISTICS

Gland packing braided by glass yarn, additionally made with PTFE, graphite and silicon oil.

### Application

AVKOPACK® 1513 is used for the sealing of pumps, mixers, valves, and sliders. It may be used in conditions of steam, neutral solutions, rarefied acids and alkali, air, inert gases, mineral oils and etc.

The packing is widely used in the power supplying industry, the chemical, cellulose industries and etc.

### Advantages

AVKOPACK® 1513 has a good flexibility, elasticity and may be installed very easy.

### Technical parameters

Working temperature:	-50°C / +280°C
Working pressure:	
- for rotary - pumps:	20 bar
- for piston - pumps:	40 bar
- for armature:	60 bar
pH:	2 – 12
V:	7 m/s
Standard dimensions:	from 4 x 4 mm to 25 x 25 mm

### Quality Control

The whole production process is supervised in accordance with the Quality System ISO 9001, ISO 14001, OHSAS 18001.

### Human hazardous

Not registered.

The information listed in this technical data sheet is based on our company's trials and experience. AVKO JSC is not to be held responsible for poor installation or application in media combining complexity of factors whose total exceeds the general qualities of the product. Our technical and sales representatives will assist any client in need of a product with a peculiar application.