

NA JOINTING SHEET AVKOPRESS B

AVKO offers ready made flat gaskets from that material.



CHARACTERISTICS

NON asbestos jointing sheets, made from high quality synthetic fibers and rubber systems.

Application

Suitable for producing of flat gaskets and garnitures for oil, water, steam, gases and non-aggressive media.

Advantages

Flexible and elastic sheets for sealing of oils and fuels at high temperatures up to 400°C and pressure 100 bars. Good recovery and compressibility of material.

Technical parameters

Dimensions:	1500x1500 mm
Thicknesses:	0.5; 0.8; 1.0; 1.5; 2.0; 2.5; 3.0; 4.0; 5.0 mm
Working temperature:	Permanent 300°C /steam 250°C/ Peak 400°C
Maximal Pressure:	100 bar
Density:	1.7 ÷ 2.0 g/cm ³
Compressability:	5-15 %
Recovery:	min 55 %
Thickness change in oil 5 h	max 3 %

* Parameters are for sheets with thickness 2 mm

Quality Control

The whole production process is supervised in accordance with the Quality System ISO 9001, ISO 14001, OHSAS 18001.

Human hazardous

Not registered.

The information listed in this technical data sheet is based on our company's trials and experience. AVKO JSC is not to be held responsible for poor installation or application in media combining complexity of factors whose total exceeds the general qualities of the product. Our technical and sales representatives will assist any client in need of a product with a peculiar application.