

NA JOINTING SHEET AVKOPRESS R

AVKO offers ready made flat gaskets from that material.

CHARACTERISTICS

NON asbestos jointing sheets, made from high quality synthetic fibers and rubber systems.

Certification

This product is certified against VDI 2440.

Application

Suitable for producing of flat gaskets and garnitures for oil, water, steam, gases and non-aggressive media.

Advantages

Oil resistant sheets for sealing at medium or low temperatures up to 250°C and pressure 80 bars. Sheets had higher hardness than other sheets, keeping values for compressibility and recovery.

Certificate VDI 2440, EN 13555, DIN 28090-1, issued by AMTEC.

Technical parameters

Dimensions:	1500x1500 mm
Thicknesses:	0.5; 1.0; 1.5; 2.0; 2.5; 3.0; 4.0; 5.0 mm
Working temperature:	Permanent 250°C Peak 300°C
Maximal Pressure:	80 bar
Density:	1.85 ÷ 2.0 g/cm ³
Compressability:	7-15 %
Recovery:	min 40 %
Thickness change in oil 5 h	≤ 2 %

* Parameters are for sheets with thickness 2 mm

Quality Control

The whole production process is supervised in accordance with the Quality System ISO 9001, ISO 14001, OHSAS 18001.

Human hazardous

Not registered.

The information listed in this technical data sheet is based on our company's trials and experience. AVKO JSC is not to be held responsible for poor installation or application in media combining complexity of factors whose total exceeds the general qualities of the product. Our technical and sales representatives will assist any client in need of a product with a peculiar application.

